

JDD DOUBLE ENVELOPE T10



Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Medium (E26)	75	03020-SU	75T10/HAL/CL	JDD	1050	120	Clear	2,000	3.58"	12/120	
		03025-SU	75T10/HAL/FR	JDD	1000	120	Frost	2,000	3.62"	12/120	
	100	03030-SU	100T10/HAL/CL	JDD	1500	120	Clear	2,000	3.7"	12/120	
		03035-SU	100T10/HAL/FR	JDD	1500	120	Frost	2,000	3.62"	12/120	
	150	03040-SU	150T10/HAL/CL	JDD	2200	120	Clear	2,000	3.55"	12/120	
		03045-SU	150T10/HAL/FR	JDD	2100	120	Frost	2,000	3.6"	12/120	
		03043-SU	150T10/HAL/CL	JDD	2050	230	Clear	2,000	4.33"	12/120	▲
	250	03050-SU	250T10/HAL/CL	JDD	4000	120	Clear	2,000	3.6"	12/120	
		03055-SU	250T10/HAL/FR	JDD	4000	120	Frost	2,000	3.65"	12/120	

JDE T4 (E26)



Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Medium (E26)	100	03065-SU	100JDE/CL/MED	JDE	1500	120	Clear	2,000	2.58"	12	
	150	03070-SU	150JDE/CL/MED	JDE	2200	120	Clear	2,000	2.81"	12	
	250	03075-SU	250JDE/CL/MED	JDE	4000	120	Clear	2,000	3.29"	12	

T4 MINI CAN (E11)



Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features	
Mini Can (E11)	35	03112-SU	Q35/CL/MC		350	120	Clear	2,000	2.13"	12/120		
		03080-SU	Q50/CL/MC		600	120	Clear	2,000	2.5"	12/120		
	50	03081-SU	Q50/FR/MC		600	120	Frost	2,000	2.4"	12/120		
		03085-SU	Q75/CL/MC		1050	120	Clear	2,000	2.44"	12/120		
	100	03090-SU	Q100/CL/MC		ESN	1500	120	Clear	2,000	2.55"	12/120	
		03440-SU	Q150/CL/MC/CD1		ESL	2200	120	Clear	2,000	2.57"	12	
		03435-SU	Q100/CL/MC/CD1		ESN	1500	120	Clear	2,000	2.57"	12	
	150	03095-SU	Q150/CL/MC		ESL	2200	120	Clear	2,000	2.72"	12/120	
		03100-SU	Q150/FR/MC		ETH	2000	120	Frost	2,000	2.68"	12	
	250	03102-SU	Q250/CL/MC/CD1		EHT	3800	120	Clear	2,000	3.11"	12/120	
		03105-SU	Q250/CL/MC		EHT	3800	120	Clear	2,000	3.11"	12/120	
	500	03110-SU	Q500/CL/MC		EVR	8000	120	Clear	2,000	3.67"	12/120	



T4 DOUBLE CONTACT (BA15D)

Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features	
Double Contact Bayonet (BA15D)	35	03111-SU	Q35/CL/DC		280	120	Clear	2,000	1.82"	12/120		
	50	03115-SU	Q50/CL/DC		500	120	Clear	2,000	2.11"	12/120		
		03114-SU	Q50/FR/DC		490	120	Frost	2,000	2.16"	12/120		
	75	03120-SU	Q75/CL/DC		1050	120	Clear	2,000	2.12"	12/120		
	100	03125-SU	Q100/CL/DC	ESR	1500	120	Clear	2,000	2"	12/120		
	150	03130-SU	Q150/CL/DC		ETC	2200	120	Clear	2,000	2.32"	12/120	
		03135-SU	Q150/FR/DC		ETF	2100	120	Frost	2,000	2.45"	12/120	
	250	03140-SU	Q250/CL/DC		ESS	4000	120	Clear	2,000	2.51"	50/120	
	500	03145-SU	Q500/CL/DC			8000	120	Clear	2,000	3.89"	50	




T4 EUROPEAN BASE (E14)

Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
European (E14)	75	03149-SU	Q75/CL/E14		1050	120	Clear	2,000	2.64"	12/120	
	100	03150-SU	Q100/CL/E14		1500	120	Clear	2,000	2.42"	12/120	
	150	03155-SU	Q150/CL/E14		2100	120	Clear	2,000	2.93"	100	
	250	03160-SU	Q250/CL/E14		4000	120	Clear	2,000	3.32"	12/120	

BI-PIN | G4 & GY6.35



Base	Watts	Item	Description	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Bi-Pin (G4)	5	03245-SU	Q5/CL/G4/12V		25	12	Clear	2,000	1.2"	12/120	
	10	03250-SU	Q10/CL/G4/12V		100	12	Clear	2,000	1.23"	12/120	
		03253-SU	Q10/FR/G4/12V		90	12	Frost	2,000	1.15"	12/120	
	20	03255-SU	Q20/CL/G4/12V		220	12	Clear	2,000	1.22"	12/120	
		03425-SU	Q20/CL/GY4/12V/CD2		220	12	Clear	2,000	1.22"	6/12	
		03258-SU	Q20/FR/G4/12V		210	12	Frost	2,000	1.15"	12	
	03260-SU	Q20/CL/G4/24V		220	24	Clear	2,000	1.2"	12		
Bi-Pin (GY6.35)	20	03263-SU	Q20/CL/GY6/12V		220	12	Clear	2,000	1.54"	12/120	
		03266-SU	Q20/CL/GY6.35/120V		120	120	Clear	2,000	1.7"	12/120	
		03265-SU	Q20/CL/GY6/120V		120	120	Clear	2,000	1.75"	12/120	
	35	03273-SU	Q35/CL/GY6.35/12V/CD2		525	12	Clear	2,000	1.54"	12/120	
		03270-SU	Q35/CL/GY6/12V		525	12	Clear	2,000	1.59"	12/120	
03275-SU	Q35/CL/GY6/120V		315	120	Clear	2,000	1.75"	12/120			



BI-PIN | GY6.35

Base	Watts	Item	Description	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Bi-Pin (GY6.35)	50	03280-SU	Q50/CL/GY6/12V	850	12	Clear	2,000	1.54"	12/120	
		03430-SU	Q50/CL/GY6/12V/CD2	900	12	Clear	2,000	1.54"	12	
		03299-SU	Q50/FR/GY6/12V	850	12	Frost	2,000	1.71"	12/120	
		03290-SU	Q50/CL/GY6/24V	600	24	Clear	2,000	1.5"	12	
		03285-SU	Q50/CL/GY6/120V/CD2	500	120	Clear	2,000	1.64"	6/60	
		03261-SU	Q50/CL/GY6/120V	500	120	Clear	2,000	1.97"	12	
	75	03295-SU	Q75/CL/GY6/12V	1350	12	Clear	2,000	1.77"	100	
		03297-SU	Q75/CL/GY6/120V	1050	120	Clear	2,000	1.75"	12/120	
	100	03300-SU	Q100/CL/GY6/12V	1900	12	Clear	2,000	1.77"	100	
		03305-SU	Q100/CL/GY6/120V	1500	120	Clear	2,000	2.06"	12	
	150	03310-SU	Q150/CL/GY6/12V	2450	12	Clear	2,000	1.71"	12/120	
		03315-SU	Q150/CL/GY6/120V	2400	120	Clear	2,000	2.31"	12/120	



BI-PIN | GY8

Base	Watts	Item	Description	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Bi-Pin (GY8)	20	21995-SU	Q20/CL/GY8/120V	120	120	Clear	2,000	1.36"	12/120	
	35	22005-SU	Q35/CL/GY8/120V	300	120	Clear	2,000	1.72"	12/120	
	50	22010-SU	Q50/CL/GY8/120V	500	120	Clear	2,000	1.56"	12/120	
	100	22015-SU	Q100/CL/GY8/120V	1500	120	Clear	2,000	1.68"	12	



BI-PIN | G9

Base	Watts	Item	Description	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Bi-Pin (G9)	25	66025-SU	Q25/CL/G9/120V	200	120	Clear	2,000	1.6"	12/120	
		66030-SU	Q25/FR/G9/120V	190	120	Frost	2,000	1.56"	12/120	
	40	66070-SU	Q40/CL/G9/120V	380	120	Clear	2,000	1.55"	12/120	
		66075-SU	Q40/FR/G9/120V	350	120	Frost	2,000	1.57"	12/120	
	50	66076-SU	Q50/CL/G9/120V	600	120	Clear	2,000	1.57"	12/120	
		66077-SU	Q50/G9/FR/120V	550	120	Frost	2000	1.57"	12/120	
	60	66035-SU	Q60/CL/G9/120V	800	120	Clear	2,000	1.55"	12/120	
		66040-SU	Q60/FR/G9/120V	720	120	Frost	2,000	1.55"	12/120	



DOUBLE ENDED T3

Base	Watts	Item	Description	Length	ASNI	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
RSC	75	03320-SU	Q75T3/CL/S	78mm		675	120	Clear	2,000	3.08"	12	
		03410-SU	Q100T3/CL/S/CD2	78mm		1000	120	Clear	1,500	3.06"	12	
100		03325-SU	Q100T3/CL/S	78mm		1000	120	Clear	1,500	3.08"	12/120	
		03330-SU	Q100T3/CL	118mm		1000	120	Clear	1,500	4.66"	12/120	
		03328-SU	Q100T3/CL/S/CD1	78mm		1000	120	Clear	1,500	3.08"	12/120	
		03335-SU	Q150T3/CL/S	78mm	J78	1950	120	Clear	1,500	3.1"	12/120	
150		03414-SU	Q150T3/CL/S/CD2	78mm		1950	120	Clear	1,500	3.06"	12	
		03411-SU	Q150T3/CL/S/CD1	78mm		1950	120	Clear	1,500	3.08"	12/120	
		03395-SU	Q150T3/CL/CD2	118mm		1950	120	Clear	1,500	4.67"	12/120	
200		03340-SU	Q150T3/CL	118mm		1950	120	Clear	1,500	4.67"	12/120	
		03350-SU	Q200T3/CL	118mm		2700	120	Clear	1,500	4.6"	12/120	
		03345-SU	Q200T3/CL/S	78mm		2800	120	Clear	1,500	3.08"	12/120	
250		03355-SU	Q250T3/CL/S	78mm		4000	120	Clear	1,500	3.08"	12/120	
300		03400-SU	Q300T3/CL/CD2	118mm	EHM	4200	120	Clear	1,500	4.67"	6	
		03402-SU	Q300T3/CL/CD1	118mm	EHM	4200	120	Clear	1,500	4.67"	12	
		03365-SU	Q300T3/CL	118mm	EHM	4200	120	Clear	1,500	4.67"	12/120	
500		03408-SU	Q500T3/CL/CD1	118mm	FCL	9000	120	Clear	2,000	4.65"	12/120	
		03370-SU	Q500T3/CL	118mm	FCL	9000	120	Clear	1,500	4.7"	12/120	
		03405-SU	Q500T3/CL/CD2	118mm	FCL	9000	120	Clear	1,500	4.65"	6	
1000		03383-SU	Q1000T3/CL/120V	254mm		19000	120	Clear	1,500	10.02"	12	▲
		03375-SU	Q1000T3/CL/3/S	189mm		19000	130	Clear	1,500	7.44"	12	
		03380-SU	Q1000T3/CL/240V	254mm		18000	240	Clear	1,500	9.99"	12/120	
1500		03388-SU	Q1500T3/CL/208V	254mm		28000	208	Clear	1,500	10.02"	12	▲
		03390-SU	Q1500T3/CL/240V	254mm		28000	240	Clear	1,500	9.99"	12	▲

MR8 MINI REFLECTOR



Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Bi-Pin (G4)	20	03194-SU	20MR8/CG/SP/12V	1,150	220	12	Cover	SP 10°	2,000	1.32"	12/120	
		03192-SU	20MR8/CG/G4/FL/12V	300		12	Cover	FL 36°	2,000	1.32"	12/120	
	35	03197-SU	35MR8/CG/G4/SP/12V	1,350	450	12	Cover	SP 10°	2,000	1.32"	12/120	
		03196-SU	35MR8/CG/G4/FL/12V	500		12	Cover	FL 36°	2,000	1.32"	12/120	
GU4	5	03445-SU	5MR11/CG/GU4/NFL/6V	250	25	6	Cover	NFL 30°	2,000	1.33"	24/120	▼



MR11 MINI REFLECTOR

Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU4	5	03445-SU	5MR11/CG/GU4/NFL/6V	JCR	250	25	6	Cover	NFL 30°	2,000	1.33"	24/120	▽
		03450-SU	5MR11/CG/GU4/NFL/12V	JCR	300	25	12	Cover	NFL 30°	2,000	1.33"	24/120	
	10	03455-SU	10MR11/CG/GU4/NFL/6V	JCR	630	80	6	Cover	NFL 30°	2,000	1.33"	24/120	▽
		03460-SU	10MR11/CG/GU4/NFL/12V	JCR	890	80	12	Cover	NFL 30°	2,000	1.3"	24/120	
	20	03195-SU	20MR11/CG/DC/NSP/12V	FST	3,300	220	12	Cover	NSP 10°	2,000	1.58"	24/120	
		03165-SU	20MR11/GU4/NSP/12V	FTB	3,300	220	12	Open	NSP 10°	2,000	1.31"	24	
		03170-SU	20MR11/GU4/NFL/12V	FTC	1,500	220	12	Open	NSP 10°	2,000	1.32"	24/120	
		03175-SU	20MR11/GU4/NFL/12V	FTD	700	220	12	Open	NFL 30°	2,000	1.33"	24/120	
		66155-SU	20MR11/CG/GU4/NFL/12V/BB	FTD	700	180	12	Cover	NFL 30°	2,000	1.31"	24/120	
		66150-SU	20MR11/CG/GU4/NFL/12V/SB	FTD	700	180	12	Cover	NFL 30°	2,000	1.31"	12	
35	03180-SU	35MR11/GU4/NSP/12V	FTE	6,000	450	12	Cover	NSP 10°	2,000	1.34"	24		
	03185-SU	35MR11/GU4/SP/12V	FTF	2,500	450	12	Open	SP 16°	2,000	1.34"	24		
	03190-SU	35MR11/GU4/NFL/12V	FTH	1,100	450	12	Open	NFL 30°	2,000	1.34"	24/120		

MR11 COLORED



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU4	20	66130-SU	20MR11/GU4/SP/12V/B	FTB	130	-	12	Blue	SP 10°	2,000	1.31"	12/120	■
		66135-SU	20MR11/GU4/SP/12V/G	FTB	270	-	12	Green	SP 10°	2,000	1.31"	12/120	■
	66140-SU	20MR11/GU4/SP/12V/O	FTB	1,300	-	12	Orange	SP 10°	2,000	1.31"	12/120	■	
	66145-SU	20MR11/GU4/SP/12V/R	FTB	500	-	12	Red	SP 10°	2,000	1.31"	12/120	■	
	66160-SU	20MR11/GU4/SP/12V/Y	FTB	1,500	-	12	Yellow	SP 10°	2,000	1.31"	12	■	

MR11 DOUBLE CONTACT & GU10



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Double Contact (BA15D)	20	03198-SU	20MR11/CG/DC/NFL/12V	FSV	2,500	220	12	Cover	NFL 30°	2,000	1.58"	24/120	
GU10	35	03193-SU	35MR11/DC/NSP/12V	GDX	6,400	450	12	Open	NSP 10°	2,000	1.58"	200	
	20	66165-SU	20MR11/CG/GU10/FL/120V	FTD	150	90	120	Cover	FL 36°	2,000	1.99"	12/120	
	35	66065-SU	35MR11/CG/GU10/FL/120V	FTH	250	220	120	Cover	FL 36°	2,000	1.85"	12/120	



MR16 MINI REFLECTOR

Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU5.3	20	03205-SU	20MR16/NSP/12V	ESX	4,500	220	12	Open	NSP 12°	2,000	1.76"	24/120	
		03203-SU	20MR16/CG/FL/12V	BAB	650	220	12	Cover	FL 38°	2,000	1.76"	12/120	
		03200-SU	20MR16/FL/12V	BAB	650	220	12	Open	FL 38°	2,000	1.76"	24/120	
	35	03218-SU	35MR16/CG/FL/12V	FMW	1,000	480	12	Cover	FL 38°	2,000	1.77"	24/120	
		03213-SU	35MR16/FL/12V	FMW	1,000	480	12	Open	FL 38°	2,000	1.76"	24/120	
		03235-SU	35MR16/CG/FL/120V	FMW	500	280	120	Cover	FL 38°	2,000	1.87"	24/120	
	50	03420-SU	50MR16/NSP/12V/CD1	EXT	8,000	765	12	Open	NSP 12°	2,000	1.79"	12	
		03215-SU	50MR16/NSP/12V	EXT	8,000	765	12	Open	NSP 12°	2,000	1.76"	24	
		03220-SU	50MR16/NFL/12V	EXZ	3,000	765	12	Open	NFL 24°	2,000	1.76"	24/120	
		03423-SU	50MR16/NFL/12V/CD1	EXZ	3,000	765	12	Open	NFL 24°	2,000	1.8"	24	
		03243-SU	50MR16/CG/FL/12V	EXN	1,500	765	12	Cover	FL 38°	2,000	1.76"	24/120	
		03207-SU	50MR16/FR/FL/12V	EXN	1,500	765	12	Frost	FL 38°	2,000	1.76"	24/120	
		03415-SU	50MR16/FL/12V/CD1	EXN	1,500	765	12	Open	FL 38°	2,000	1.76"	12/120	
		03210-SU	50MR16/FL/12V	EXN	1,500	765	12	Open	FL 38°	2,000	1.76"	24/120	
		03237-SU	50MR16/CG/FL/24V	EXN	1,250	615	24	Cover	FL 38°	2,000	1.76"	24/120	
		03240-SU	50MR16/CG/FL/120V	EXN	750	420	120	Cover	FL 38°	2,000	1.9"	24/120	
75	03225-SU	75MR16/NSP/12V	EYF	1,150		12	Open	NSP 12°	2,000	1.76"	24		
	03230-SU	75MR16/FL/12V	EYC	1,150		12	Open	FL 38°	2,000	1.76"	24/120		
GY8	20	66015-SU	20MR16/CG/GY8/FL/120V	BAB	200	90	120	Cover	FL 38°	2,000	1.77"	24/120	
	50	66125-SU	50MR16/CG/GY8/FL/120V	EXN	550	470	120	Cover	FL 38°	2,000	1.77"	12/120	



MR16 SILVER & BLACK BACK

Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU5.3	20	66000-SU	20MR16/CG/FL/12V/BB	BAB	650	180	12	Cover	FL 38°	2,000	1.75"	12	
		66005-SU	20MR16/CG/FL/12V/SB	BAB	650	180	12	Cover	FL 38°	2,000	1.75"	12	
	35	66170-SU	35MR16/CG/FL/12V/BB	FMW	1,000	390	12	Cover	FL 38°	2,000	1.75"	12/120	
		66060-SU	35MR16/CG/FL/12V/SB	FMW	1,000	390	12	Cover	FL 38°	2,000	1.77"	12/120	
	50	66020-SU	50MR16/CG/NFL/12V/BB	EXZ	3,500	630	12	Cover	NFL 24°	2,000	1.75"	12/120	
		66045-SU	50MR16/CG/NFL/12V/SB	EXZ	3,500	630	12	Cover	NFL 24°	2,000	1.75"	12	
		66080-SU	50MR16/CG/FL/12V/BB	EXN	1,500	630	12	Cover	FL 38°	2,000	1.77"	12/120	
		66105-SU	50MR16/CG/FL/12V/SB	EXN	1,500	630	12	Cover	FL 38°	2,000	1.77"	12/120	

MR16 COLORED



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU5.3	50	66085-SU	50MR16/NSP/12V/B	EXT	960	-	12	Blue	NSP 12°	2,000	1.77"	12/120	
		66090-SU	50MR16/NSP/12V/G	EXT	2,480	-	12	Green	NSP 12°	2,000	1.77"	12/120	
		66095-SU	50MR16/NSP/12V/O	EXT	4,000	-	12	Orange	NSP 12°	2,000	1.77"	12/120	
		66100-SU	50MR16/NSP/12V/R	EXT	3,200	-	12	Red	NSP 12°	2,000	1.77"	12/120	
		66110-SU	50MR16/NSP/12V/Y	EXT	6,400	-	12	Yellow	NSP 12°	2,000	1.77"	12	

MR16 GU10



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU10	20	66010-SU	20MR16/GU10/FL/120V	BAB	150	90	120	Cover	FL 38°	2,000	2.09"	24/120	
	35	03232-SU	35MR16/CG/GU10/FL/120V	FMW	450	220	120	Cover	FL 38°	2,000	2.09"	24/120	
	50	66050-SU	50MR16/GU10/NFL/120V	EXZ	900	385	120	Cover	NFL 24°	2,000	2.09"	24/120	
		03233-SU	50MR16/CG/GU10/FL/120V	EXN	800	385	120	Cover	FL 38°	2,000	2.09"	24/120	

MR16 SILVER & BLACK BACK GU10



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
GU10	35	66055-SU	35MR16/CG/GU10/FL/120V/BB	FMW	450	220	120	Cover	FL 38°	2,000	2.07"	12	
		66175-SU	35MR16/CG/GU10/FL/120V/SB	FMW	450	220	120	Cover	FL 38°	2,000	2.08"	24	
	50	66115-SU	50MR16/CG/GU10/FL/120V/BB	EXN	800	370	120	Cover	FL 38°	2,000	2.1"	12/120	
		66120-SU	50MR16/CG/GU10/FL/120V/SB	EXN	800	385	120	Cover	FL 38°	2,000	2.08"	12/120	

MR16 JDR REFLECTOR



Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Inter-mediate (E17)	50	03480-SU	50JDR/N/MED/FL/120V	JDR	500	470	120	Open	FL 38°	2,000	2.79"	12	
	75	03000-SU	75JDR/N/MED/FL/120V	JDR	1,200	750	120	Open	FL 38°	2,000	2.95"	12	
	100	03010-SU	100JDR/N/MED/FL/120V	JDR	1,500	N/A	120	Open	FL 38°	2,000	2.95"	25	
Medium (E26)	50	03475-SU	50JDR/MED/FL/120V	JDR	500	470	120	Open	FL 38°	2,000	2.69"	12	
	75	03005-SU	75JDR/MED/FL/120V	JDR	1,200	750	120	Open	FL 38°	2,000	2.69"	12	
	100	03015-SU	100JDR/MED/FL/120V	JDR	1,500	N/A	120	Open	FL 38°	2,000	2.74"	12	



MR16 JDR | MEDIUM

Base	Watts	Item	Description	ASNI	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	50	03470-SU	50MR16/MED/FL/120V	EXN	500	385	120	Cover	FL 38°	2,000	2.13"	25/250	



PAR16 REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	45	24100-SU	45PAR16/HAL/NFL	480		120	Clear	NFL 30°	2,000	3.09"	15	
		24010-SU	60PAR16/HAL/NSP	3000		120	Clear	NSP 10°	2,000	3.07"	15	
	60	24000-SU	60PAR16/HAL/NFL	650	420	120	Clear	NFL 30°	2,000	3.09"	15	
		24060-SU	75PAR16/HAL/NSP	5800		120	Clear	NSP 10°	2,000	3.07"	15	
	75	24050-SU	75PAR16/HAL/NFL	1400		120	Clear	NFL 30°	2,000	3.07"	15	



PAR20 REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	39	26000-SU	39PAR20/HAL/SP	2400	520	120	Clear	SP 10°	1,500	3.1"	15	
		26005-SU	39PAR20/HAL/NFL	1100	520	120	Clear	NFL 30°	1,500	3.1"	15	
	50	25050-SU	50PAR20/HAL/NFL/B	-	-	120	Blue	NFL 30°	2,000	3.1"	15	
		25055-SU	50PAR20/HAL/NFL/G	-	-	120	Green	NFL 30°	2,000	3.1"	15	
		25060-SU	50PAR20/HAL/NFL/R	-	-	120	Red	NFL 30°	2,000	3.1"	15	
		25065-SU	50PAR20/HAL/NFL/Y	-	-	120	Yellow	NFL 30°	2,000	3.1"	15	



PAR30 REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	39	26010-SU	39PAR30/HAL/SP	2400	520	120	Clear	SP 10°	1,500	3.48"	15	
		26020-SU	39PAR30/HAL/FL	900	520	120	Clear	FL 35°	1,500	3.52"	15	
	50	25102-SU	50PAR30/HAL/NFL	850		120	Clear	NFL 30°	2,000	3.49"	15	
		25101-SU	50PAR30/HAL/FL/3	850		130	Clear	FL 40°	2,000	3.49"	15	
		25125-SU	50PAR30/HAL/NSP	2680		120	Clear	NSP 9°	2,000	3.49"	15	
		60	26025-SU	60PAR30/HAL/SP	12000	1080	120	Clear	SP 10°	1,000	3.49"	15
26035-SU	60PAR30/HAL/FL		1250	1080	120	Clear	FL 35°	1,000	3.48"	15		



PAR30 COLORED

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	75	25160-SU	75PAR30/HAL/NFL/G	-	-	120	Green	NFL 30°	2,000	3.49"	15	■
		25170-SU	75PAR30/HAL/NFL/Y	-	-	120	Yellow	NFL 30°	2,000	3.57"	15	■



PAR30 LONG NECK REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	60	26055-SU	60PAR30/LN/HAL/SP	12000	1080	120	Clear	SP 10°	1,080	4.62"	15	
	39	26045-SU	39PAR30/LN/HAL/NFL	1100	520	120	Clear	NFL 25°	1,500	4.65"	15	
	60	26065-SU	60PAR30/LN/HAL/FL	1250	1080	120	Clear	FL 35°	1,080	4.6"	15	



PAR38 REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	39	26070-SU	39PAR38/HAL/NFL	1100	520	120	Clear	NFL 25°	1,500	5.14"	15	
	60	26080-SU	60PAR38/HAL/FL	1250	1080	120	Clear	FL 35°	1,000	5.13"	15	
	70	26085-SU	70PAR38/HAL/SP	15000	1310	120	Clear	SP 10°	1,000	5.2"	15	
		26087-SU	70PAR38/HAL/FL	1500	1340	120	Clear	FL 35°	1000	5.14"	15	
	80	26097-SU	80PAR38/HAL/NFL	3500	1590	120	Clear	NFL 25°	1,000	5.16"	15	



R20 REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	45	25262-SU	45R20/HAL/ECO/FL		550	120	Frost	FL	1,500	3.85"	12/24	



BR30 REFLECTOR

Base	Watts	Item	Description	CBCP	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Medium (E26)	60	25251-SU	60BR30/HAL/FL	720	120	Frost	FL 75°	2,000	5.02"	24	
		25252-SU	60BR30/HAL/FL/3	720	130	Frost	FL 75°	2,000	5.02"	24	



AR70 ALUMINUM REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
Double Contact Bayonet (BA15D)	20	21505-SU	20AR70/FL/12V	800	180	12	Aluminum	FL 24°	2,000	1.97"	12	
		21500-SU	20AR70/SP/12V	1,500	180	12	Aluminum	SP 8°	2,000	2"	12/48	
	50	21515-SU	50AR70/FL/12V	2,500	600	12	Aluminum	FL 24°	2,000	2.13"	12/120	
		21510-SU	50AR70/SP/12V	11,000	600	12	Aluminum	SP 8°	2,000	2"	12/120	



AR111 ALUMINUM REFLECTOR

Base	Watts	Item	Description	CBCP	Lumens	Volts	Finish	Beam Spread	Hours	Mol	Pkg.	Features
G53	35	21525-SU	35AR111/FL/12V	850	390	12	Aluminum	FL 24°	2,000	2.25"	12/60	
		21520-SU	35AR111/SP/12V	13,500	390	12	Aluminum	SP 8°	2,000	2.15"	12	
	50	21535-SU	50AR111/FL/12V	3,800	630	12	Aluminum	FL 24°	2,000	2.25"	12/60	
		21530-SU	50AR111/SP/12V	17,000	630	12	Aluminum	SP 8°	2,000	2.15"	12/60	
	75	21545-SU	75AR111/FL/12V	6,000	870	12	Aluminum	FL 24°	2,000	2.25"	12	
		21550-SU	75AR111/WFL/12V	1,650	870	12	Aluminum	WFL 45°	2,000	2.16"	12	
		21540-SU	75AR111/SP/12V	30,000	870	12	Aluminum	SP 8°	2,000	2.15"	12	



A TYPE

Base	Watts	Item	Description	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Medium (E26)	28	25135-SU	28A/HAL/CL	430	120	Clear	1,500	4.2"	12/120	
		25140-SU	28A/HAL/SW	400	120	Frost	1,500	4.2"	120	
	42	25136-SU	42A/HAL/CL	750	120	Clear	1,500	4.2"	12/120	
		25141-SU	42A/HAL/SW	710	120	Frost	1,500	4.2"	12/120	
	53	25137-SU	53A/HAL/CL	1050	120	Clear	1,500	4.2"	12/120	
		25142-SU	53A/HAL/SW	1000	120	White	1,500	4.2"	12/120	
	72	25138-SU	72A/HAL/CL	1490	120	Clear	1,500	4.2"	12/120	
		25143-SU	72A/HAL/SW	1490	120	Frost	1,500	4.2"	12/120	



BT15

Base	Watts	Item	Description	Lumens	Volts	Finish	Hours	Mol	Pkg.	Features
Medium (E26)	60	25192-SU	60BT15/WH	800	120	White	2,000	4.2"	12/48	
		25193-SU	60BT15/WH/TS	800	120	White - Tuff Skin	2,000	4.2"	12/48	
	75	25195-SU	75BT15/WH	1000	120	White	2,000	4.2"	12/48	
	100	25196-SU	100BT15/WH	1500	120	White	2,000	4.2"	12/48	
	150	25198-SU	150BT15/WH	2100	120	White	2,000	4.2"	12/48	
		25199-SU	150BT15/WH/TS	2100	120	White - Tuff Skin	2,000	4.2"	12/48	